

Product Highlights

Performance

- 7160-32CQ: 32x 100GbE
- 7160-48YC6: 48x 25GbE and 6x 100GbE
- 7160-48TC6: 48x 10GBASE-T and 6x 100GbE
- Up to 32 wire-speed 100GbE ports
- Up to 6.4 terabits per second
- Up to 2.4 billion packets per second
- Wire speed L2 and L3 forwarding

Data Center Optimized Design

- Fully shared 24MB packet buffer
- Programmable pipeline for application specific encapsulation
- Adaptable forwarding tables with custom profiles
- Over 94% efficient power supplies
- 1+1 redundant & hot-swappable power
- N+1 redundant & hot-swappable fans
- Front-to-rear or rear-to-front cooling
- Tool less rails for simple installation

Virtualization and Provisioning

- CloudVision
- VXLAN Routing for next generation DC
- LANZ for burst and flow monitoring
- VM Tracer
- Zero Touch Provisioning (ZTP)
- Advanced Event Monitoring
- sFlow (RFC3176)
- Hierarchical time-stamping and PTP

Cloud Networking Ready

- Arista AlgoMatch™
- 128K MAC Addresses
- 64K IPv4 and 32K IPv6 Host Routes
- Over 500K IPv4 Routes
- Up to 48K Access list entries

Resilient Control Plane

- High Performance x86 CPU
- 8GB DRAM
- 4GB Flash
- User applications can run in a VM

Arista Extensible Operating System

- Single binary image
- Fine-grained truly modular network OS
- Stateful Fault Containment (SFC)
- Stateful Fault Repair (SFR)
- Full access to Linux shell and tools
- Extensible platform - bash, python, C++ , GO, OpenConfig


Overview

The Arista 7160 Series are key components of the Arista 7000 Series portfolio of data center switches. Highly dynamic cloud data center networks continue to evolve with the introduction of new protocols and server technologies such as containers bringing with them ever increasing bandwidth demands, accelerating the need for dense 25 and 100 Gigabit Ethernet switching in both leaf and spine tiers of modern networks. The Arista 7160 Series are purpose built fixed configuration 10/25GbE and 100GbE systems built for the highest performance environments, and to meet the needs of the largest scale data centers. They combine scalable L2 and L3 resources and high density with a highly programmable and customizable switch architecture. Simple software updates allow reconfiguration of packet parsing, lookups, traffic scheduling, packet modification and traffic monitoring without re-engineering of the switch.

The 7160 can be deployed in a range of open networking solutions including large scale layer 2 and layer 3 cloud designs, overlay networks, virtualized or traditional enterprise data center networks.

The 7160 Series are available in a range of models with a choice of 10GBASE-T and 25GbE SFP with 40/100GbE QSFP uplinks and a 40/100GbE system that offers up to 32 ports of wire speed 100GbE in a 1RU system. The wide range of interfaces and density choice provides deployment flexibility.

25GbE interfaces with SFP and 100GbE with QSFP on the 7160 Series enables flexible choices of port speed providing unparalleled flexibility and the ability to seamlessly transition data centers to the next generation of Ethernet performance. The 7160 Series provide industry leading power efficiency with airflow choices for back to front, or front to back. Combined with Arista EOS the 7160 Series delivers advanced features for cloud, big data, virtualized and traditional designs.



Arista 7160 Series of Data Center Switches

Arista EOS

All Arista products including the 7160 Series runs the same Arista EOS software, binary image simplifying network administration with a single standard across all switches. Arista EOS is a modular switch operating system with a unique state sharing architecture that cleanly separates switch state from protocol processing and application logic. Built on top of a standard Linux kernel, all EOS processes run in their own protected memory space and exchange state through an in-memory database. This multi-process state sharing architecture provides the foundation for in-service-software updates and self-healing resiliency together with stateful switchover without the loss of data plane forwarding.

Arista EOS enables advanced monitoring and automation capabilities such as Zero Touch Provisioning, LANZ, VM Tracer and Linux based tools to be run natively on the switch.

Software Defined Cloud Networks

Arista Software Defined Cloud Networking (SDCN), combines the principles that have made cloud computing the unstoppable force that it is: automation, self service provisioning, and linear scaling of both performance and economics coupled with the trend in Software Defined Networking that delivers: network virtualization, custom programmability, simplified architectures, and lower capital expenditure. This combination creates a best-in-class software foundation for maximizing the value of the network to both the enterprise and service provider data center. A new architecture for the most mission-critical location within the IT infrastructure that simplifies management and provisioning, speeds up service delivery, lowers costs and creates opportunities for competitive differentiation, while putting control and visibility back in the hands of the network and systems administrators.

The Four Pillars of Arista's Software Defined Cloud Networking:

Universal Cloud Network

- Scalable standards-based MLAG at Layer 2, ECMP for Layer 3 and VXLAN for network virtualization flexibility
- Non blocking leaf-spine for 10K-100K hosts

Cloud Control

- Standards based EOS with AEM, ZTP/ZTR, LANZ and DANZ
- Automated Monitoring for visibility and telemetry

Network Wide Virtualization

- Multi-vendor API Support with eAPI
- Support for VMWare and NSX with VXLAN and VMTracer
- Support for Microsoft OMI and Openstack OVSDB

Network Applications and Automated Management

- Single point of network-wide state with Arista CloudVision
- Networked applications for workload mobility, smart systems rollback and upgrades and workflow telemetry
- Open Partner integration

Scaling Data Center Performance

The Arista 7160 Series deliver switching capacity that enables dramatically faster and simpler network designs for data centers and lowers both capital and operational expenses. The Arista 7000 Series of fixed and modular systems with a single consistent EOS allows for flexible selections at all tiers of the network and deployment scenarios including layer 2 MLAG, layer 3 ECMP, VXLAN Overlay, and Internet route scale.

Arista's **Multi-Chassis Link Aggregation (MLAG)** technology supports a leaf and spine active/active L2 network topology. An **Equal Cost Multi-Path (ECMP)** design at Layer 3 scales the network in a fully non-blocking, low-latency, two-stage network that provides predictable and consistent application performance. The flexibility of the L2 and L3 multi-path design options combined with support for open standards provides maximum flexibility, scalability and network wide virtualization that scales to hundreds of thousands of hosts in a single two-tier design. Both designs support overlay networks via VXLAN and can integrate with standards-based overlay controller solutions.

AlgoMatch ^(TM)

AlgoMatch is a unique Arista innovation for modern cloud networks, combining both software and hardware to enable more flexible and scalable solutions for access control, policy based forwarding and network telemetry. By combining general purpose memory with with advanced software algorithms AlgoMatch delivers higher scale, performance and efficiency with lower power and is more cost effective than traditional solutions. AlgoMatch provides a more efficient packet matching algorithm that in turn enables flow matching for access control, policy and visibility. The net benefits are a high performance policy engine with both increased functionality and scale in a cost and power efficient solution.

- AlgoMatch enables IPv4 and IPv6 access control at the same scale
- L4 rule ranges are programmed efficiently without expansion or reduced capacity
- Multiple actions can be performed on a single packet or flow
- User defined filters allow flexible packet classification based on offsets for custom actions
- Supports rich policy with consistent semantics that would exhaust classical resources

Enhanced Features for High Performance Cloud Networks

The Arista 7160 delivers a suite of advanced traffic control and monitoring features to improve the agility of modern high performance environments, with solutions for automation, data monitoring, precise timing and next-generation virtualization.

Automating the data center enables customers to dynamically provision computing resources in the most efficient manner while also meeting business needs by maintaining service level agreements (SLAs). Arista EOS automates complex IT workflows and simplifies network operations while reducing or even eliminating downtime. Arista EOS rich automation capabilities not only reduce the human error element in network operations but also enable IT operators to make the network work the way they want.

Arista offers solutions for a variety of approaches to cloud-like network automation. Addressing the needs of the largest public cloud environments as well as applying those lessons learned in the turnkey CloudVision automation offering.

CloudVision

CloudVision is a network-wide approach for workload orchestration and workflow automation as a turnkey solution for Cloud Networking. CloudVision extends the EOS publish subscribe architectural approach across the network for state, topology, monitoring and visibility. This enables enterprises to move to cloud-class automation without needing any significant internal development.

Arista Event Management (AEM)

Advanced Event Management (AEM), a sub-system of Arista EOS, is a powerful and flexible tool to automate tasks and customize the behavior of EOS and the operation of the overall data center switching infrastructure. Simplifying the overall operations, AEM provides the tools to customize alerts and actions. AEM allows operators to fully utilize the intelligence within EOS to respond to real-time events, automate routine tasks, and automate actions based on changing network conditions.

Flexible Profiles

Network scalability is directly impacted by a switches forwarding tables. The 7160 Series provide flexibility on how memory resources are allocated among the different tables and features. A Forwarding Profile is a pre-defined allocation of the forwarding table resources to assign specific table sizes. Forwarding profiles allows the available resources to be optimally allocated for specific features or set of features for a given use case. This allows for deployment of the 7160 Series across multiple use cases each configured with a different forwarding profile to suit the unique requirements.

Programmable Pipeline

The 7160 programmable packet pipeline allows the addition of new protocols, encapsulation and tunneling features to the packet processor through simple software upgrades without changes to the underlying hardware. This allows for rapid testing and deployment avoiding costly replacements or major upgrades. A recent example of a new encapsulation in the data center environment is VXLAN which required new silicon technology, delaying customer deployments and innovation.

Virtualization




Supporting next-generation virtualized data centers requires tight integration with orchestration tools and emerging encapsulation technologies such as VXLAN. The 7160 builds on the valuable tools already provided by the Arista VM Tracer suite to integrate directly into encapsulated environments. Offering a wire-speed gateway between VXLAN and traditional L2/3 environments, the 7160 makes integration of non-VXLAN aware devices including servers, firewalls and load-balancers seamless and provides the ability to leverage VXLAN as a standards based L2 extension technology for non-MPLS environments.

Maximum Network Design Flexibility

- Scalable designs with up to a 128-way ECMP provides flexibility and balances traffic evenly across the largest leaf-spine designs
- MLAG designs are effective at almost any layer of the network and maximize cross-sectional bandwidth with fast failover times measured in 100's of milliseconds for link failures.
- VXLAN gateway, bridging and routing with VMTracer features to enable next generation data center designs
- Wide choice of interfaces with broad support for flexible 10GbE, 25GbE or 50GbE modes.
- Support for standards based IEEE 25GbE with mix and match support for both 10G and 25G for simple and cost effective migration
- AlgoMatch to match business intent to network policy for flow matching, access control and telemetry
- Flexible forwarding profiles for optimal allocation of L2 and L3 forwarding table resources in multiple use cases
- EOS tools for network wide visibility and monitoring to detect traffic bursts, monitor latency and congestion and allow capacity planning to improve application performance and availability

System Overview

The 7160 Series deliver unprecedented levels of programmability, flexible forwarding profiles, and a fully shared packet buffer in a choice of high density interfaces as shown below to seamlessly evolve to the next generation of Ethernet speeds.

	<p>7160-48TC6: 48 port 10GbE BASE-T and 6 port 100G QSFP</p> <ul style="list-style-type: none"> - Easy migration from 1000Mb to 1G/10G using a familiar RJ45 connection - Six 100G QSFP ports allow choice of 6x 100GbE, 24x 25GbE, 6x 40GbE, or 24x 10GbE - 5 speeds for flexible 10GbE, 25GbE, 40GbE, 50GbE and 100GbE with optics or cables - 2.16Tbps of wire speed performance with 24MB of buffer -
	<p>7160-48YC6: 48 port 25G SFP and 6 port 100G QSFP</p> <ul style="list-style-type: none"> - Offer 48 wirespeed 10/25G ports with 6 100G ports for up to 72 total 25G or 10G ports - Easy migration from 1/10G to 1/10/25G using a familiar SFP connection - Six 100G QSFP ports allow choice of 6x 100GbE, 24x 25GbE, 6x 40GbE, or 24x 10GbE - 5 speeds for flexible 10GbE, 25GbE, 40GbE, 50GbE and 100GbE with optics or cables - 3.6Tbps of wire speed performance with 24MB of buffer
	<p>7160-32CQ: 32 port 100G QSFP</p> <ul style="list-style-type: none"> - Offers a choice of port combinations with 40G and 100G QSFP optics and cables - Flexible interface combinations - 32x 100G/40G, 128x 25/10G, 64x 50G - 100G QSFP ports for 5 speeds for flexible 10GbE, 25GbE, 40GbE, 50GbE and 100GbE - 6.4Tbps of wire speed performance with 24MB of buffer

Arista 7160 Flexible Combinations

The Arista 7160 lowers total cost of ownership as they are designed to be efficient with power per port as low as 10W per 100GbE port which combined with front to rear cooling to optimize the data center environment produces the most reliable, dense and power efficient 100GbE fixed configuration switch.





7160 Advanced Traffic Manager and Fully Shared Buffer

The 7160 Series each incorporate an advanced traffic manager with 24MB of packet buffer that is fully shared across all ports. Unlike other architectures that have fixed per-port packet memory or buffers arranged in multiple slices the 7160 Series buffer is dynamically allocated across all ports with the ability to adjust in real time to the demands of bursty applications, mixed speeds and congestion. Extensive support for Active Queue Management mechanisms such as WRED, DCTCP and ECN ensure that high priority flows and lossless storage traffic are handled equally well with the ability to absorb large bursts with extensive counters for visibility and accounting.

7160 High Availability

The Arista 7160 switches were designed for continuous operations with system wide monitoring of both hardware and software components, simple serviceability and provisioning to prevent single points of failure. Key high availability features include:

- 1+1 hot-swappable power supplies and four hot-swap fans provide dynamic temperature control combined with N+1 redundancy
- Color coded PSU's and fans that deliver platinum level power efficiency
- Live software patching
- Self healing software with Stateful Fault Repair (SFR)
- Smart System Upgrade (SSU) and Accelerated Software Update (ASU) *

		
<p><i>7160-32CQ Rear View: Rear to Front</i></p>	<p><i>Hot swap fan modules</i></p>	<p><i>Hot swap power supplies</i></p>
		
<p><i>7160-48YC6 and 7160-48TC6 Rear View: Front to Rear</i></p>		

Layer 2 Features

- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree Protocol
- Rapid Per Vlan Spanning Tree (RPVST+)
- 4096 VLANs
- Q-in-Q *
- 802.3ad Link Aggregation/LACP
 - 64 Ports / Channel
 - 128 groups per system
- MLAG (Multi-Chassis Link Aggregation)
 - Uses IEEE 802.3ad LACP
 - 128 ports per MLAG
- 802.1Q VLANs/Trunking
- 802.1AB Link Layer Discovery Protocol
- 802.3x Flow Control
- Jumbo Frames (9216 Bytes)
- IGMP v1/v2/v3 snooping
- Storm Control *
- 802.1 AVB *
- SMPTE-2059-2 *

Layer 3 Features

- Static Routes
- Routing Protocols: OSPF, OSPFv3, BGP, MP-BGP, IS-IS, and RIPv2
- 128-way Equal Cost Multipath Routing (ECMP)
- VRF
- Bi-Directional Forwarding Detection (BFD)
- Unicast Reverse Path Forwarding (uRPF) *
- VRRP
- Virtual ARP (VARP)
- Policy Based Routing (PBR) *
- Route Maps

Multicast

- IGMP v2/v3
- Protocol Independent Multicast (PIM-SM / PIM-SSM)
- PIM-BiDir *
- Anycast RP (RFC 4610)
- Multicast Source Discovery Protocol (MSDP)

Advanced Monitoring and Provisioning

- Latency Analyzer and Microburst Detection (LANZ)
 - Configurable Congestion Notification (CLI, Syslog) *
 - Streaming Events (GPB Encoded) *
 - Capture/Mirror of congested traffic *
- Zero Touch Provisioning (ZTP)
- Advanced Mirroring
 - Port Mirroring (16 sessions)
 - Enhanced Remote Port Mirroring
 - Mirror to EOS/SSD
 - SPAN/TAP M:N Aggregation *
 - L2/3/4 Filtering *
- Advanced Event Management suite (AEM)
 - CLI Scheduler
 - Event Manager
 - Event Monitor

- Linux tools
- Integrated packet capture/analysis with TCPDump
- Restore and Configure from USB
- RFC 3176 sFlow
- Optional SSD for logging and data capture
- IEEE 1588 PTP *

Virtualization Support

- VXLAN Routing and Bridging
- VM Tracer VMware Integration

Security Features

- ACLs using L2, L3, L4 fields
- ACL Logging and Counters
- Atomic ACL Hitless restart
- Control Plane Protection (CPP)
- PDP
- Service ACLs
- DHCP Relay
- MAC Security
- TACACS+
- RADIUS
- ARP trapping and rate limiting

Quality of Service (QoS) Features

- Up to 8 queues per port
- Strict priority queueing
- 802.1p based classification
- DSCP based classification and remarking *
- Egress shaping / Weighted round robin (WRR)
- Policing / Shaping
- Rate limiting *
- Explicit Congestion Notification (ECN) marking
- 802.1Qbb Per-Priority Flow Control (PFC)
- 802.1Qaz Enhanced Transmission Selection (ETS) *
- Data Center Bridging Extensions (DCBX)

Network Management

- CloudVision
- Configuration rollback and commit
- 100/1000 Management Port
- RS-232 Serial Console Port
- USB Port
- SNMP v1, v2, v3
- Management over IPv6
- Telnet and SSHv2
- Syslog
- AAA
- Industry Standard CLI
- Beacon LED for system identification
- System Logging
- Environment monitoring

* Not currently supported in EOS

Extensibility

- Linux Tools
 - Bash shell access and scripting
 - RPM support
 - Custom kernel modules
- Software Defined Networking (SDN)
 - eAPI
 - OpenStack Neutron Support
- Programmatic access to system state
 - Python
 - Chef
 - Puppet
 - C++
 - eAPI
 - GO
 - OpenConfig
 - OpenStack Neutron Plug-in support
- Native KVM/QEMU support

Standards Compliance

- 802.1D Bridging and Spanning Tree
- 802.1p QOS/COS
- 802.1Q VLAN Tagging
- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree Protocol
- 802.1AB Link Layer Discovery Protocol
- 802.3ad Link Aggregation with LACP
- 802.3x Flow Control
- 802.3ab 1000BASE-T
- 802.3z Gigabit Ethernet
- 802.3ae 10 Gigabit Ethernet
- 802.3by 25 Gigabit Ethernet
- 802.3ba 40 Gigabit Ethernet
- 802.3ba 100 Gigabit Ethernet
- RFC 2460 Internet Protocol, Version 6 (IPv6) Specification
- RFC 2461 Neighbor Discovery for IP Version 6 (IPv6)
- RFC 2462 IPv6 Stateless Address Autoconfiguration
- RFC 2463 Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification
- IEEE 1588-2008 Precision Time Protocol

SNMP MIBs

- RFC 3635 EtherLike-MIB
- RFC 3418 SNMPv2-MIB
- RFC 2863 IF-MIB
- RFC 2864 IF-INVERTED-STACK-MIB
- RFC 2096 IP-FORWARD-MIB
- RFC 4363 Q-BRIDGE-MIB
- RFC 4188 BRIDGE-MIB
- RFC 2013 UDP-MIB
- RFC 2012 TCP-MIB
- RFC 2011 IP-MIB
- RFC 2790 HOST-RESOURCES-MIB
- RFC 3636 MAU-MIB
- RMON-MIB
- RMON2-MIB

- HC-RMON-MIB
- LLDP-MIB
- LLDP-EXT-DOT1-MIB
- LLDP-EXT-DOT3-MIB
- ENTITY-MIB
- ENTITY-SENSOR-MIB
- ENTITY-STATE-MIB
- ARISTA-ACL-MIB
- ARISTA-QUEUE-MIB
- RFC 4273 BGP4-MIB
- RFC 4750 OSPF-MIB
- ARISTA-CONFIG-MAN-MIB
- ARISTA-REDUNDANCY-MIB
- RFC 2787 VRRPv2MIB
- MSDP-MIB
- PIM-MIB
- IGMP-MIB
- IPMROUTE-STD-MIB
- SNMP Authentication Failure trap
- ENTITY-SENSOR-MIB support for DOM (Digital Optical Monitoring)
- User configurable custom OIDs

See EOS release notes for latest supported MIBs

Table Sizes

STP Instances	64 (MST)/510 (RPVST+)
IGMP Groups	128K
Ingress ACLs	48K
ECMP	128-way
MAC Addresses	128K
IPv4 Host Routes	64K
IPv4 Multicast (S,G)	32K
IPv6 Host Routes	32K
IPv4 Routes - Unicast	128K
IPv6 Routes - Unicast	64K

* Not currently supported in EOS

Model Comparison	7160-32CQ	7160-48YC6	7160-48TC6
Ports	32 x 100G QSFP	48 x 25G SFP 6 x 100G QSFP	48 x 10G-T 6 x 100G QSFP
Max 100GbE Ports	32	6	6
Max 50GbE Ports	64	12	12
Max 40GbE Ports	32	6	6
Max 25GbE Ports	128	72	24
Max 10GbE Ports	128	72	72
Throughput	6.4Tbps	3.6Tbps	2.16Tbps
Packets/Second	2.4Bpps (1.2Bpps)	2.4Bpps (1.2Bpps)	2.4Bpps (1.2Bpps)
Latency	From 2us	From 2us	From 3us
CPU	Quad-Core x86	Quad-Core x86	Quad-Core x86
System Memory	8 GB (32G optional)	8 GB	8 GB
Flash Storage Memory	4 GB	4 GB	4 GB
Packet Buffer Memory	24MB Fully shared	24MB Fully shared	24MB Fully shared
SSD Storage (optional)	Optional	No	No
100/1000 Mgmt Ports	1	1	1
RS-232 Serial Ports	1 (RJ-45)	1 (RJ-45)	1 (RJ-45)
USB Ports	1	2	2
Hot-swap Power Supplies	2 (1+1 redundant)	2 (1+1 redundant)	2 (1+1 redundant)
Hot-swappable Fans	4 (N+1 redundant)	4 (N+1 redundant)	4 (N+1 redundant)
Reversible Airflow Option	Yes	Yes	Yes
Rack Units	1U	1U	1U
Size (WxHxD)	19 x 1.75 x 16" (48.3 x 4.4 x 40.6cm)	19 x 1.75 x 16" (48.3 x 4.4 x 40.6cm)	19 x 1.75 x 16" (48.3 x 4.4 x 40.6cm)
Typical/Max Power Draw	310W / 465W	168W / 382W	408W / 482W
Weight	19.2lbs (8.7kg)	19.24lbs (8.7kg)	20.42lbs (9.3kg)
Power Supplies	500W AC 500W DC	500W AC 500W DC	500W AC 500W DC
AlgoMatch	Yes	Yes	Yes
EOS Feature Licenses	LIC-FIX-2	LIC-FIX-2	LIC-FIX-2
Minimum EOS Version	4.18.0	4.18.0	4.18.1

Typical power consumption measured at 25C ambient with 50% load on all ports

Supported Optics and Cables

Interface Type	SFP+ ports
10GBASE-CR	SFP+ to SFP+: 0.5m-5m
10GBASE-AOC	SFP+ to SFP+: 3m-30m
10GBASE-SRL	100m
10GBASE-SR	300m
10GBASE-LRL	1km
10GBASE-LR	10km
10GBASE-ER	40km
10GBASE-ZR	80km
10GBASE-DWDM	80km
1GbE SX/LX/TX	Yes

Interface Type	100G QSFP ports
100GBASE-SR4	70m OM3 / 100m OM4 Parallel MMF
100GBASE-SWDM4	70m OM3 / 100m OM4 Duplex MMF
100GBASE-SRBD	70m OM3 / 100m OM4 Duplex MMF
100GBASE-LR4/LRL4	10km/2km SM Duplex
100GBASE-CWDM4	2km SM duplex
100GBASE-PSM4	500m SM Parallel
100GBASE-AOC	1m to 30m
100GBASE-ERL4	40km SM Duplex
100GBASE-CR4	QSFP to QSFP: 1m to 5m
25GBASE-CR	QSFP to SFP25: 1m to 3m lengths

Environmental Characteristics

Operating Temperature	0 to 40°C (32 to 104°F)
Storage Temperature	-40 to 70°C (-40 to 158°F)
Relative Humidity	5 to 95%
Operating Altitude	0 to 10,000 ft, (0-3,000m)

Power Supply Specifications

Power Supply	PWR-500AC	PWR-500-DC
Input Voltage	100-240AC	40-72V DC
Typical Input Current	6.3 - 2.3A	13.1 - 7.3A 11A at -48V
Input Frequency	50/60Hz	DC
Input Connector	IEC 320-C13	AWG #16-#12
Efficiency (Typical)	93% Platinum	90%
Compatibility	7160 Series	7160 Series

Interface Type	40G QSFP ports
10GBASE-CR	0.5m-5m QSFP+ to 4x SFP+ (see note 1)
40GBASE-CR4	QSFP+ to QSFP+: 0.5m-5m
40GBASE-AOC	3m to 100m
40GBASE-UNIV	150m (OM3) / 150m (OM4), 500m (SM)
40GBASE-SRBD	100m (OM3) / 150m (OM4)
40GBASE-SR4	100m (OM3) / 150m (OM4)
40GBASE-XSR4	300m (OM3) / 400m (OM4)
40GBASE-PLRL4	1km (1km 4x10G LR/LRL)
40GBASE-PLR4	10km (10km 4x10G LR/LRL)
40GBASE-LRL4	1km
40GBASE-LR4	10km
40GBASE-ER4	40km

Interface Type	25G SFP ports
25GBASE-CR	SFP25 to SFP25: 1m-5m
25GBASE-AOC	SFP+ to SFP+: 3m-30m
25GBASE-SR	70m
25GBASE-LR	10km

Standards Compliance

EMC	Emissions: FCC, EN55022, EN61000-3-2, EN61000-3-3 or EN61000-3-11, EN61000-3-12 (as applicable) Immunity: EN55024 Emissions and Immunity: EN300 386
Safety	UL/CSA 60950-1, EN 60950-1, IEC 60950-1 CB Scheme with all country differences
Certifications	North America (NRTL) European Union (EU) BSMI (Taiwan) C-Tick (Australia) CCC (PRC) MSIP (Korea) EAC (Customs Union) VCCI (Japan)
European Union Directives	2006/95/EC Low Voltage Directive 2004/108/EC EMC Directive 2011/65/EU RoHS Directive 2012/19/EU WEEE Directive

* Not currently supported in EOS

Product Number	Product Description
DCS-7160-32CQ-F	Arista 7160, High Capacity 32 x 100GbE QSFP switch, front to rear air, 2 x AC and 2 x C13-C14 cords
DCS-7160-32CQ-R	Arista 7160, High Capacity 32 x 100GbE QSFP switch, rear to front air, 2 x AC and 2 x C13-C14 cords
DCS-7160-32CQ#	Arista 7160, High Capacity 32 x 100GbE QSFP switch, configurable fans and psu
DCS-7160-32CQ-M#	Arista 7160, High Capacity 32 x 100GbE QSFP switch, SSD, configurable fans and psu
DCS-7160-48YC6-F	Arista 7160, High Capacity 48 x 25GbE SFP and 6 x 100GbE QSFP switch, front to rear air, 2 x AC and 2 x C13-C14 cords
DCS-7160-48YC6-R	Arista 7160, High Capacity 48 x 25GbE SFP and 6 x 100GbE QSFP switch, rear to front air, 2 x AC and 2 x C13-C14 cords
DCS-7160-48YC6#	Arista 7160, High Capacity 48 x 25GbE SFP and 6 x 100GbE QSFP switch, configurable fans and psu
DCS-7160-48TC6-F	Arista 7160, High Capacity 48x10GbE RJ45 (1/10G) and 6 x 100GbE QSFP switch, front to rear air, 2 x AC and 2 x C13-C14 cord
DCS-7160-48TC6-R	Arista 7160, High Capacity 48x10GbE RJ45 (1/10G) and 6 x 100GbE QSFP switch, rear to front air, 2 x AC and 2 x C13-C14 cords
DCS-7160-48TC6#	Arista 7160, High Capacity 48x10GbE RJ45 (1/10G) and 6 x 100GbE QSFP switch, configurable fans and psu

Optional Components and Spares

PWR-500AC-F	Spare 500 Watt AC power supply for Arista 7050X, 7160 and 7280R 1RU Switches (front-to-rear airflow)
PWR-500AC-R	Spare 500 Watt AC power supply for Arista 7050X, 7160 and 7280R 1RU Switches (rear-to-front airflow)
PWR-500-DC-F	Spare 500 Watt DC power supply for Arista 7050X, 7160 and 7280R 1RU Switches (front-to-rear airflow)
PWR-500-DC-R	Spare 500 Watt DC power supply for Arista 7050X, 7160 and 7280R 1RU Switches (rear-to-front airflow)
LIC-FIX-2-E	Enhanced L3 License for Arista Fixed switches, 40-132 port 10G (BGP, OSPF, ISIS, PIM, NAT)
LIC-FIX-2-V	Virtualization license for Arista Fixed switches 40-132 port 10G (VMTracer and VXLAN)
LIC-FIX-2-Z	Monitoring & provisioning license for Arista Fixed switches 40-132 port 10G (ZTP, LANZ, TapAgg, API, Time-stamping)
LIC-FIX-2-FLX-L	FLX-Lite License for Arista Fixed switches Group 2 - Full Routing Up to 256K Routes, EVPN, VXLAN, SR, base MPLS LSR (no TE or link/node protection)
FAN-7000-F	Spare fan module for Arista 7150, 7124SX(FX), 7050, 7160, 7280 & 7048-A switches (front-to-rear airflow)
FAN-7000-R	Spare fan module for Arista 7150, 7124SX(FX), 7050, 7160, 7280 & 7048-A switches (rear-to-front airflow)
FAN-7000H-F	Spare fan module for Arista 7280R & 7160-48TC6 1RU switches (front-to-rear airflow)
FAN-7000H-R	Spare fan module for Arista 7280R & 7160-48TC6 1RU switches (rear-to-front airflow)
KIT-7001	Spare accessory kit for Arista 1RU tool-less switches
KIT-2POST-1U-NT	Spare 1RU 2 post rail kit for 1RU tool less systems (7050QX-32S, 7050SX/TX, 7160 and 7280R)
KIT-4POST-NT	Spare 1RU/2RU tool-less rail kits for 4-post installation (7050QX-32S, 7050SX/TX, 7280R, 7160 and 7250X)

Note:

- Front-to-rear means the air flows from the switch port side to the fan side. Rear to front means the air flows from the fan side to the switch port side.

Warranty

The Arista 7160 Series switches come with a one-year limited hardware warranty, which covers parts, repair, or replacement with a 10 business day turn-around after the unit is received.

Service and Support

Support services including next business day and 4-hour advance hardware replacement are available. For service depot locations, please see: <http://www.arista.com/en/service>

Headquarters

5453 Great America Parkway
Santa Clara, California 95054
408-547-5500

Support

support@arista.com
408-547-5502
866-476-0000

Sales

sales@arista.com
408-547-5501
866-497-0000