

FrontCultivator



**Front mounted
harrow**

3.0 – 6.0 m working width

The **FrontCultivator** is a front mounted all-round implement, capable of handling numerous in-field challenges. It is possible to make a “double” stubble preparation in one pass by, for example, mounting a MaxiDisc behind the tractor. This could be a great advantage in grass land and in fields with heavy residues. The **FrontCultivator** is extremely efficient in cultivating the stubble and loosening the soil to a depth of 30 cm.



To achieve a precise working depth the Cultivator is mounted with a chain instead of a top link. The flexible chain makes the implement work freely via the carrying wheels and the front linkage.



The **FrontCultivator** comes as standard with hydraulic stone protection. This provides huge advantages and ensures efficient work even under the most difficult conditions.



The implement is supported by 2 wheels. The mechanical depth adjustment is easily achieved.



To avoid a ridge of soil to the side of the machine spring loaded discs are mounted on either side. The Discs can be adjusted in height by the turn of a spindle.



The implement is mounted with the new developed 2-D tine, which turns 20 cm horizontal and 30 cm vertical.

Technical specifications:

Working width	Nos. tines	Wheels	Weight	HP required from
3.0 m	9 pcs.	2 pcs.	1.350 kg	80 hp
4.0 m	13 pcs.	2 pcs.	1.610 kg	100 hp
4.0 m H	13 pcs.	2 pcs.	1.925 kg	100 hp
6.0 m H	19 pcs.	2 pcs.	2.350 kg	160 hp

DALBO - ROBUST AND RELIABLE