

Aurea basic

Steel wheelbarrow with handle grip, Ø 30 x 1,5 mm tubular frame, 0,8 mm-thick welded and painted pressed tray, capacity Lt 70

- ART. 1003** Ø 350 mm pneumatic wheel, 1 mm-thick steel rim
- ART. 1004** Ø 350 mm wheel with solid rubber tyre, 1 mm-thick steel rim



Aurea strong

Steel wheelbarrow strong type, Ø 30 x 1,5 mm tubular frame, 1 mm-thick welded and painted pressed heavy tray, capacity Lt.70

- ART. 1005** Ø 350 mm pneumatic wheel, 1 mm-thick steel rim
- ART. 1006** Ø 350 mm wheel with solid rubber tyre, 1 mm-thick steel rim



Aurea basic partially disassembled

Steel wheelbarrow partially disassembled with handle grip, Ø 30 x 1,5 mm tubular painted frame, 0,9 mm-thick pressed galvanized tray, capacity Lt 70

- ART. 1015** Ø 350 mm pneumatic wheel, 1 mm-thick steel rim
- ART. 1016** Ø 350 mm wheel with solid rubber tyre, 1 mm-thick steel rim



Aurea with PVC tray

Wheelbarrow with Ø 30 mm painted, tray capacity Lt 100.

- ART. 18444** Ø 350 mm pneumatic wheel



Aurea tipper

Steel wheelbarrow with tipping handles, Ø 30 x 1,5 mm tubular frame, 0,8 mm-thick welded and painted pressed tray, capacity Lt 70

- ART. 1007** Ø 350 mm pneumatic wheel, 1 mm-thick steel rim
- ART. 1008** Ø 350 mm wheel with solid rubber tyre, 1 mm-thick steel rim



Technical information and using instruction are given with this wheelbarrow, in conformity with european rules
CE Bench Mark





■ Heavy wheelbarrow

Iron frame "U" shape,
tinfoil tray painted completely
welded thickness 1,2mm

ART. 1009 Ø 350 mm pneumatic wheel,
steel rim

ART. 1010 Ø 350 mm pneumatic wheel,
steel rim



■ Heavy tipper wheelbarrow

Iron frame "U" shape, tinfoil tray painted
completely welded thickness 1,2 mm,
with tipping handles

ART. 1011 Ø 350 mm pneumatic wheel,
steel rim

ART. 1012 Ø 350 mm pneumatic wheel,
steel rim



■ Totally disassembled steel wheelbarrow

Tubular frame Ø 30 mm x 1,5mm,
epoxy powder painted,
painted tray 1mm thickness Lt 90 capacity

ART. 1019 Ø 380 mm pneumatic wheel

ART. 1020 wheel with solid rubber tyre



■ Totally disassembled steel wheelbarrow

Tubular frame Ø 30 mm x 1,5mm,
epoxy powder painted,
galvanized tray 1mm thickness Lt 90 capacity

ART. 1021 Ø 380 mm pneumatic wheel

ART. 1022 wheel with solid rubber tyre



■ Trays for Aurea wheelbarrows

ART. 4010 Tray for Aurea Basic Lt 70 - thickness 0,8 mm

ART. 4011 Tray for Aurea Basic Partially disassembled Lt 70
thickness 0,9 mm

ART. 4020 Tray for Aurea Strong Lt 75 - thickness 1 mm

ART. 4030 Tray for Aurea Tipper Lt 70 - thickness 0,8 mm



■ Wheels for Aurea wheelbarrows

ART. 5100 Ø 350 X 80 mm, pneumatic wheel
for wheelbarrow Aurea 1 mm-thick steel rim

ART. 5200 Ø 350 X 80 mm, wheel with solid rubber tyre,
1 mm-thick steel rim

