



# MIX 4000 CS / 6000 CS

Feed Mixer for salt and concentrate



*Ideal for supplementing free range cattle.*



FACTORY ITAPIRA, SP



FROM BRAZIL TO ALL CONTINENTS OVER 50 COUNTRIES



FACTORY SÃO JOÃO DA BOA VISTA, SP

Mixers Line  
JF, the solution for the farmer!



# MIXERS LINE

**JF Mix 4000/6000 CS** is a feed mixer for salt and concentrate, built entirely in stainless steel. It is extremely resistant, specially the parts in contact with abrasive and oxidating materials. Equipped with rubber cleaners in the mixing paddles, it doesn't leave leftovers at the bottom of the tank, avoiding waste of expensive feed.

It has an exclusive mixing system and a joystick control for discharge flow adjustment. It also features the scale DG 5000 system with multi-recipe programming and downloadable info to computers. It is the feed mixer ideal for free range cattle system, making it possible to supplement directly in the field.



**CONVEYOR DISCHARGE**



**STANDARD EXTRACTOR**



**JF MIX 6000 CS WITH EXTENDED EXTRACTOR**

## Advantages

- High resistance due to 5 mm stainless steel sheet construction;
- Homogeneous mixing;
- It transports and discharges directly into the trough without wasting material;
- Ideal for free range livestock systems;
- Multi-recipe capable;
- Easy handling;
- Discharge with flexible tube;

Stainless steel 5mm

**INOX**

Rain protection cover



Joystick control for flow adjustment



Flotation tyres

Scale with downloadable information



## Features

- 5 mm stainless steel sheet body;
- Mixing paddle system;
- Joystick control for flow adjustment;
- Scale with downloadable information;
- Scale with multi-recipe system;
- Equipped with rain protection cover;
- Conveyor kit and extended extractor optional;

TECHNICAL FEATURES	JF MIX 4000 CS	JF MIX 6000 CS
Power source	tractor PTO	tractor PTO
Height standard and conveyor	2450mm	2450mm
Height extended work/transport	4120mm / 2600mm	4120mm / 2600mm
Length	3800mm	4800mm
Capacity <sup>1</sup>	4m <sup>3</sup>	6m <sup>3</sup>
Discharge side	left	left
Width	2650mm	2650mm
Weight (empty)	1937 kg	2230 kg
Tires	400/60 R15,5 (HF75) (T404)	400/60 R15,5 (HF75) (T404)
Required power at PTO	50 to 60 cv	50 to 60 cv
Required revolution at PTO	540 RPM	540 RPM
<b>Stainless steel</b>	Tank/Mixing paddles and discharge auger	Tank/Mixing paddles and discharge auger

<sup>1</sup>The load capacity can vary depending on the product's density.



The technical data and images are only for guidance purposes. In an effort to provide products that meet customer needs, the JF reserves the right to update them at any time without prior notice.

JF Máquinas Agrícolas

jfmaquinasoficial

JFMaquinasAgrícolas

[www.jfmaquinas.com](http://www.jfmaquinas.com)

Rua Santa Terezinha, 921  
Jd. Guarujá - Itapira/SP Brazil  
Zip Code 13973-900  
+55 (19) 3863-9644