

Kögel Asphalt Tipper Trailer



Temperature Sensor

- Simple maintenance of the temperature sensor system via the sheet metal covers
- Simple replacement



Protection the running lines

- Temperature sensors
- Control line for the sliding roof



Bluetooth Printer (optional)

- Traceability of the order
- Fulfilling of the documentation obligation in accordance with legal stipulations



Temperature indication unit

- Indication of four individual measuring points
- Indication of average temperature

Kögel Equipment Characteristics Asphalt Tipper Trailer

Swinging tailgate	Round load body	3-axle version	2-axle version	Off-road axle
■	■	■	■	■
24 m ³ / 27 m ³ Body	Floor thickness 4/5/6 mm		Side wall thickness 3/4/5 mm	
■	■		■	




Electrical tipper cover (optional)

- Protects aggregate from getting wet and/or being chilled
- Optimal load securing: Provides protection against losing the load and increases road safety
- Can be safely operated from the ground using a remote control
- Polyurethane (optional)



Roll-up cover with control pedestal (optional)

- Roll-up cover with a foldaway transverse tarpaulin bow, operated via a crank and round winding shaft
- Attach toolbox, water container and/or fire extinguisher in a space-saving manner
- Ascent optionally on left or right
- Silicone tarpaulin (optional)



Hinged underride guard

- Also suitable for paver use as a result of the folding underride guard
- Clear reduction in contamination by asphalt



Chute

- 170 millimeters extended overhang of the trough
- Optional chute no longer required
- Perfect for road paver use



Long-life corrosion protection

- High-quality surface finish with nano-ceramic plus KTL coating for the frame and the tipper body
- Galvanised sheet metal layer, powder coated in RAL colours to customer choice



Sliding access ladder (optional)

- Sliding access ladder on the trough end wall (in combination with an electric sliding roof)
- Ensures simple and safe entry and exit into and out of the trough



Locking hook

- Sturdy and robust execution
- Fully lowering tailgate locking hook
- Perfect protection from contamination and falling rocks



Neatly arranged control unit

- User-oriented layout
- Control unit for automatic lowering ensures stability against overturning
- Easily accessible push-buttons on the spring-loaded parking brake and the EBS diagnostics connections
- Smart-Board (optional)
- Temperature indication unit
4x Individual Temperature
1x Average Temperature

KÖGEL

Kögel Trailer GmbH & Co. KG | Industriestraße 1 | 89349 Burtenbach | Germany
 fon +49 8285 88-0 | fax +49 8285 88-17905 | info@koegel.com
www.koegel.com

Safety instruction! The trailer may only be used subject to express compliance with all road traffic, Employer's liability insurance association and load-securing technology regulations. Illustrations may show optional extra equipment and the products are subject to continuous technical modifications. No liability is accepted for mistakes or printing errors. Printed in Germany. Reprinting not permitted 08/16.