MAMMUT 3 AXLES Low Bed Semi Trailer (KM 779-K)





Product: 3 Axles Low Bed Semi trailer (KM 779-K)

Dimensions:

Length: 15,000 mm Width: 3,200 mm

Deck length: 10,500 mm Trailer Weight: 14,500 kgs Max. Payload: 60,000 kgs

Chassis Structure:

All welded steel construction to ST 52.3/ QST 380 Tm Longitudinal member of hot rolled of grade ST 52-3, all Parts are made from pressed steel.

Floor Structure:

Floor is made from 6mm chequered plate which is welded to cross member and chassis.

Axles / Suspension:

3x 16 tons BPW® (Germany) axle.

"VBT" Type with Multi-Leaf underslung spring suspension

Tyres/Rim:

12 nos. 12.00 x R20" - (Foreigner)

12 nos. 8.5 x 20" Tri-lex rims (Germany)

Landing Gear:

Multi speed adjustable landing legs, 50 tons: Statistic capacity, 24 tons: Dynamic capacity (JOST Germany).

King Pin:

+GF+ or JOST® 3.5" dia.(280KN) with related coupling According to SAE Standard.

Braking system:

Knorr®/Wabco® (Germany) 'S' Cam type drum brakes. Operated by 2 line air system acting on all wheels incorporating automatic load sensing valves. and service/emergency relay valves air resorvoir, manual parking brake.

Electrical:

7 and 15 Pole quick release connector, Pair of 24 volts rear light, side light and alarming system From Aspock with LED type.

Painting:

Grit blasted to SA 2.5 Acid washed. Coated with Anti - oxid epoxy. Final coat with polyurethane color according to customer choice.

Accessories:

Spare wheel carrier with derrick - Holder for fire extinguisher - Iron wheel chock (2nos) - Spare wheel carrier mounting (2nos) - Air tank 80 lit - Water tank mounting - Special rear door jac (2 nos) - Tool box - Back spring ramp (2 nos) - Lashing hook

Options:

Spare Tyre & Rim - stainless steel water tank

