

nokian[®]
TYRES

NOKIAN TRACTOR KING



REVOLUTIONARY FROM SURFACE TO CORE

Nokian Tractor King is a no-compromise tractor tyre for the heaviest of machinery and the most difficult terrain in forestry, earthmoving and road construction. The design from all-new tread pattern to fortified carcass is nothing short of revolutionary in a tractor tyre.



DURABILITY

Core and sidewall designed for top-class puncture-resistance in toughest conditions.

TRACTION

Wide tread and radically increased amount of tractive edges for grip on all terrains.

TAKES HEAVY LOADS

Innovatively wear-resistant tread design for comfortable, economical kilometres.

HIGH LOAD CAPACITY

Up to 320 kPa

50 % MORE TRACTIVE EDGES

Compared to conventional lug pattern

HIGH SPEED CATEGORY

65 km/h (D)



RADIAL



TUBELESS



STEEL BELTED



CCR



ARAMID SIDEWALLS



PUNCTURE PROTECTION



CHAIN USE



STUDDABLE



STONE EJECTORS



“Top-class traction and lateral grip – even on slippery rocks”

CHRISTOF WIEDERSTEIN
Hergenroth / Germany

TECHNICAL SPECIFICATIONS

Size	LI / SS	Recommended rim	Permitted rims	Width		Diameter		Loaded static radius		Rolling circumference		SRI	Inflation pressure for load capacity calculation		Load Capacity kg / lbs										Max. Inflation pressure		Product code		
				mm	in	mm	in	mm	in	mm	in		kPa	psi	65 km/h	40 mph	50 km/h	30 mph	40 km/h	25 mph	30 km/h	20 mph	20 km/h	10 mph	10 km/h	5 mph		kPa	P.s.i.
500/65R28	150 D	DW16L	DW15L, TW15L, DW18L, TW18L	503	19.8	1361	53.6	629	24.8	4103	161.5	650	320	46	3350	7385	3520	7760	3670	8090	3850	8490	4120	9085	5030	11090	400	58	T445673
540/65R28	154 D	DW18L	DW16L, TW16L, TW18L	550	21.7	1413	55.6	650	25.6	4248	167.2	675	320	46	3750	8265	3940	8685	4110	9060	4310	9500	4610	10165	5630	12410	400	58	T445674
600/60R28	157 D	DW18L	TW18L, DW20B, TW20B	601	23.7	1431	56.3	617	24.3	4255	167.5	675	320	46	4125	9095	4330	9545	4520	9965	4740	10450	5070	11175	6190	13645	400	58	T445675
540/65R30	155 D	DW18L	DW16L, TW16L, TW18L	550	21.7	1464	57.6	677	26.7	4427	174.3	700	320	46	3875	8545	4070	8975	4240	9350	4460	9835	4770	10515	5810	12810	400	58	T445676
540/70R30	159 D	DW18L	DW16L, TW16L, TW18L	540	21.3	1518	59.8	693	27.3	4539	178.7	725	320	46	4375	9645	4590	10120	4790	10560	5030	11090	5380	11860	6560	14460	400	58	T445677
600/70R30	165 D	DW18L	TW18L, DW20B, TW20B	591	23.3	1602	63.1	730	28.7	4826	190.0	750	320	46	5150	11355	5410	11925	5640	12435	5920	13050	6330	13955	7730	17040	400	58	T445678
620/75R30	169 D	DW20B	TW20B	625	24.6	1692	66.6	770	30.3	5097	200.7	800	320	46	5800	12785	6090	13425	6350	14000	6670	14705	7130	15720	8700	19180	400	58	T445679
600/65R34	163 D	DW18L	TW18L, DW20B, TW20B	591	23.3	1644	64.7	754	29.7	4960	195.3	775	320	46	4875	10745	5120	11290	5940	11775	5610	12370	6000	13230	7310	16115	400	58	T445680
600/70R34	167 D	DW18L	TW18L, DW20B, TW20B	591	23.3	1704	67.1	775	30.5	5138	202.3	800	320	46	5450	12015	5720	12610	6370	13160	6270	13825	6700	14770	8180	18035	400	58	T445681
600/65R38	165 D	DW18L	TW18L, DW20B, TW20B	591	23.3	1745	68.7	805	31.7	5282	208.0	825	320	46	5150	11355	5410	11925	5640	12435	5920	13050	6330	13955	7730	17040	400	58	T445682
650/65R38	169 D	DW20B	TW20B	645	25.4	1811	71.3	830	32.7	5480	215.7	875	320	46	5800	12785	6090	13425	6350	14000	6670	14705	7130	15720	8700	19180	400	58	T445683
650/75R38	175 D	DW20B	TW20B, DW21B, TW21B, DW23B, TW23B	645	25.4	1941	76.4	885	34.8	5889	231.9	925	320	46	6900	15210	7250	15985	7560	16665	7940	17505	8490	18715	10350	22820	400	58	T445684
650/85R38	178 D	DW20B	TW20B, DW21B, TW21B, DW23B, TW23B	645	25.4	2071	81.5	944	37.2	6267	246.7	975	320	46	7500	16535	7880	17370	8210	18100	8630	19025	9230	20350	11250	24800	400	58	T445685
710/70R42	179 D	DW23B	TW23B, DW25B, TW25B	716	28.2	2061	81.1	943	37.1	6235	245.5	975	320	46	7750	17085	8140	17945	8490	18715	8910	19645	9530	21010	11630	25640	400	58	T445686
710/75R42	181 D	DW23B	TW23B, DW25B, TW25B	716	28.2	2133	84.0	972	38.3	6458	254.3	1025	320	46	8250	18190	8660	19090	9030	19910	9490	20920	10150	22375	12380	27295	400	58	T445687

In forestry or heavy road use add 40 kPa / 6 psi