



**SANOK RUBBER**

---

**V-BELTS PRODUCTION RANGE**

# SINGLE BELTS

## Narrow section

Section	Approximate dimensions		Length range [mm]	Additional length [mm]	Designation
	Width [mm]	Height [mm]			
SPZ	9,7	8	760 - 3000	537; 562; 578; 612; 637; 662; 687; 700; 712; 719; 721; 737	Ld (datum length)
SPA	12,7	10	1220 - 5000	732; 757; 782; 807; 832; 857; 882; 932; 957; 982; 1007; 1032; 1057; 1082; 1107; 1132; 1157; 1182; 1207	Ld (datum length)
SPB	16,3	13	1250 - 10000		Ld (datum length)
SPC	22	18	1750 - 18000		Ld (datum length)
13,4x10,7	13,4	10,7	1240 - 3000		Ld (datum length)

Section	Approximate dimensions		Length range [inch]	Designation
	Width [mm]	Height [mm]		
5V	15,5	13	50" - 393"	La (outside length)
8V	25	23	129" - 492"	La (outside length)

## Classical section

Section	Approximate dimensions		Length range [mm]	Additional length [mm]	Designation
	Width [mm]	Height [mm]			
Z	10	6	760 - 3000	500; 530; 560; 582; 600; 630; 670; 710; 750	Ld (datum length)
A	13	8	760 - 5000	500; 530; 560; 600; 630; 670; 710; 750	Ld (datum length)
B	17	11	760 - 10000	630; 670; 710; 750	Ld (datum length)
20x12,5	20	12,5	1220 - 10000		Ld (datum length)
C	22	14	1220 - 18000		Ld (datum length)
25x16	25	16	1300 - 10000		Ld (datum length)
D	32	19	2000 - 18000		Ld (datum length)
HDM	32	16	1800 - 6096		La (outside length)
E	38	23	4350 - 18000		Ld (datum length)
36x23,5	36	23,5	3200 - 6096		Li (inside length)

## 3L, 4L, 5L

Section	Approximate dimensions		Length range [inch]	Designation
	Width [mm]	Height [mm]		
3L	9,5	5,5	31" - 61"	La (outside length)
4L	12,7	7,9	31" - 98"	La (outside length)
5L	16,6	9	31" - 98"	La (outside length)

## Wide section

Section	Approximate dimensions		Length range [mm]	Additional length [mm]	Designation
	Width [mm]	Height [mm]			
HI	25,4	12,7		2265	Ld (datum length)
HJ	31,9	15,1	1250 - 3000	1181	Ld (datum length)
HK	38,1	17,5	1600 - 5000		Ld (datum length)
HL	44,5	19,8	3190 - 6096	1940; 2070; 2180; 2310; 2345; 2544; 2830; 3186	Ld (datum length)
HM	50,8	22,2	3190 - 6096	1540; 1777; 1882; 2052; 2072; 2130; 2222; 2265; 2310; 2415	Ld (datum length)
62x25	62	25		2136; 2300; 2325*	Ld (datum length)

\* 62x25-2325 – only version with aramid cords available

# SINGLE BELTS

**Double-  
-sided**

Section	Approximate dimensions		Length range [mm]	Designation
	Width [mm]	Height [mm]		
HAA	13	10,5	1250 - 4070	Le (effective length)
HBB	17	13,5	1750 - 5000	Le (effective length)
HCC	22	17,5	1800 - 6096	Le (effective length)

**Flat drive**

Section	Approximate dimensions		Length range [mm]	Designation
	Width [mm]	Height [mm]		
120x5	120	5	1950 - 6096	Li (inside length)
140x5	140	5	1950 - 5000	Li (inside length)
140x7	140	7	1950 - 5000	Li (inside length)
150x5	150	5	1900 - 5000	Li (inside length)

The belts between 30 - 135 mm width are available on request.

# POWER BANDS (joined belts)

**Classical  
section**

Section	Approximate dimensions		Length range [mm]	Designation
	Width [mm]	Height [mm]		
A BP	15,88	10,1	1250 - 3064	Le (effective length)
B BP	19,05	13,5	1250 - 10000	Le (effective length)
C BP	25,4	17	2000 - 10000	Le (effective length)

**Narrow section**

Section	Approximate dimensions		Length range [mm]	Designation
	Width [mm]	Height [mm]		
SPA BP	15	12,5	1250 - 5000	Ld (datum length)
SPB BP	19,05	16,7	1800 - 10000	Ld (datum length)
SPC BP	25,5	22,9	2200 - 10000	Ld (datum length)

Section	Approximate dimensions		Length range [inch]	Designation
	Width [mm]	Height [mm]		
5V BP	17,5	16,7	59" - 240"	Le (effective length)

# RAW-EDGE COGGED BELTS

Wide section raw-edge cogged

Section	Approximate dimensions		Length range [mm]	Designation
	Width [mm]	Height [mm]		
28x16	28	16	1450	Ld (datum length)
30x13	30	13	1680	Li (inside length)
30x15	30	15	1680	Li (inside length)
38x18	38	18	1440	Li (inside length)
38x18	38	18	1500	Ld (datum length)
40x12	40	12	1360	Li (inside length)
40x13	40	13	920	La (outside length)
HL	45	20	1920; 2362; 3186; 3200	Ld (datum length)
HM	50	22	1860; 2052; 2072; 2130; 3215	Ld (datum length)
50,8x24	51	24	2270	Ld (datum length)
55x22	55	22	1860	Ld (datum length)
55x22	55	22	2021	Li (inside length)
55x25	55	25	1800	Ld (datum length)
55x25	55	25	2285	Li (inside length)
59x23	59	23	2161	La (outside length)
62x25	62	25	2078; 2136; 2390	Ld (datum length)
63x26	63	26	2290	La (outside length)
63x27	63	27	2115	Ld (datum length)
68x24	68	24	2485	Li (inside length)
68x24	68	24	2600	Ld (datum length)
74x30*	74	30	2611	La (outside length)

\* 74x30 is raw-edge double cogged (inner and outer surfaces are cogged)



Sanok Rubber Company S.A.  
 Poland, 38-500 Sanok, ul. Przemyska 24  
 tel.: +48 13 46 54 444  
 e-mail: kontakt@sanokrubber.pl

[www.sanokrubber.pl](http://www.sanokrubber.pl)