

SAFE & DRY

QUICK CEMENT POWDER TRANSPORT




V-TYPE CEMENT SEMI-TRAILER

www.serin.com.tr

 **SERİN**

V-TYPE CEMENT SEMI-TRAILER



30 m3 V-TYPE CEMENT SEMI-TRAILER

Length & Truck Tractor Type	11300 mm suitable for 6x4 & 4x2 Truck Tractor
Width	2550 mm
Height of the silobas (bulk trailer)	4000 mm
Chassis	The chassis of the silobas semi-trailer is integrated with connection parts welded to the body of the tank shell.
King Pin	2"king – pin detachable from below made by, SAE standards 8 bolt type.
Loading Capacity	30 m3
Axles	3 x 12000 kg carrying capacity SERRIN brand
Tank Construction	Tank is "V" shape. Tank is built by carbon steel ST37 with thickness of 4 mm
Manhole Covers	3 units, 450 mm diameter heavy duty screw type loading covers (top loading cover)
Discharging Valves	1 unit leaf valve, 1 unit ball valve for speeding the discharging and 4 " discharging system
Hoses and Connections	6 mt special alloy discharge hose and 2 unit regulated to 2.5 bar safety valve and inside the tank including 150 mm diameter with air conduit imported hose. Upper catwalk and Access ladder is set to trailer
Safety Accessories	Upper catwalk and Access ladder is set to trailer
Brake & Suspension System	Air Suspension, Drum Brake System, Wabco ABS or EBS Brake System
Landing Gear	Double Speed, 24000 kg carrying capacity, Jost, SAF or SERRIN brand mechanical Landing Gears
Rear Bumper	Suitable 70/225 / AT-version of the rear bumper
Checks and Protective Barriers	Carriers with 1 unit wheel check
Tires and Rims	6 +1 PCS 385 / 65 R 22.5 Goodyear, Pirelli, Bridgestone or Equivalent.
Spare Wheel Carrier	1 piece tire carrier
Boxes	1 unit Tool Box, 1 units of 6 kg of fire tube and plastic carriers
Water Tank	60 lit water tank which is made of stainless steel
Paint	The metal surfaces of the vehicle after the welding process is cleaned with sand shot blasting process with grit metal. In order to protect the surfaces from rusting on the top of the surfaces with 2 coats of epoxy primer and acrylic finished paint will be RAL (9003) or will on customer demand. The total thickness of the paint work is 120 micron.
Electrical System	3 units side (gabbler amber) lights and the rear side (park, brake and stop amber lights) Reflector triangles, Electrical system; Flame proof electrical system, 2 X 7-pin electrical socket.
Accessories	Hub key, Axles Bolt Nut key, Tool box keys
Type of the Compressor	3 Head 7300 debi lt/dk. Compressor DEUTZ MOTOR (DIESEL)
OPTIONALS	Electrical Compressor 2 Headed 7.200 Bar, Volumes: 25-27-30-32-35-37-40 m3 , Axles: SAF or BFW Brand



+90 332 444 29 23

www.serrin.com.tr

f /serrintreyler

whatsapp /serrin_treyler

instagram /serrintreyler



TSEK



TUV AUSTRIA

TUV AUSTRIA

TUV AUSTRIA

TRUCKER ASSOCIATION

SERIN

Serrin Treyler A.Ş.
Sancak Mah. Yeni Istanbul Cad.
No:138 Sancaktepe / KADIKÖY
Tel : 00 332 292 01 00
Fax : 00 332 292 01 05
Mail : serrin@serrin.com.tr
Web : www.serrin.com.tr



Serrin Treyler A.Ş. reserves the right of making changes in the technical specifications and components without making any prior notice. Some components seen on the photographs and specifications seen here may not be standard features of the vehicles. There may have been some changes after publication of this document (February 2015). No right can be claimed on a sign or numbers used by seller or buyer to define a product in ordering. Differences in colors are due to printing techniques.