

LIGHT TRUCK



UN-331

- Double steel-belted construction for long-lasting wear and uniformity.
- Jointless spiral-wrapped full nylon cap for added strength and stability.
- Rib-type tread design with deep shoulder grooves provides all-season capability.
- Continuous shoulder ribs provide smooth, even tread wear and increased tread life.
- Premium rubber compound and extra plies resist cuts, punctures and abrasions.
- Extra heavy-duty sidewall construction delivers responsive handling and performance under demanding commercial applications.

Tire Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl. Pressure (psi)
185R14C	6PR	650	187	5.5	1708	55
	8PR	650	187	5.5	1874	65



UN-332

- Rib-type tread design and half-square shoulder design, enhance wear performance, avoid bias-wear.
- Low-noise pattern design delivers silence and comfort.
- Higher carcass and belt design, increase rigidity to afford tire loading and high Speed.

Tire Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl. Pressure (psi)
195R15C	6PR	689	195	5.5	1930	55
	8PR	689	195	5.5	2094	65



UN-335

- Designed for all-position light truck tyre for city and highway service
- Longer tyre life
- Straight rib design makes excellent resistance to irregular wear and lower tyre noise

Tire Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl. Pressure (psi)
7.00R16C	10PR	776	194	5.5	2491	75

Tire Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl. Pressure (psi)
7.50R16C	12PR	807	209	6	3020	94



UN-337

- Offers high maneuverability with confident cornering control and stands up to extreme wear with its straight rib design.
- 4-rib design is good for drain and brake in the wet condition.

Tire Size	Ply Rating	Overall Diameter (mm)	Section Width (mm)	Rim Width (inch)	Max. Load (lbs)	Max. Infl. Pressure (psi)
195/75R16C	8PR	698	196	5.5	2149	65
	10PR	698	196	5.5	2335	76